



- 1 -

## INFLATOR

## Cross-Reference to Related Applications

[0001] This Nonprovisional application claims priority under 35 U.S.C. § 119(e) on U.S. Provisional Application No. 60/404,925 filed on August 22, 2002 and under 35 U.S.C. § 119(a) on Patent Application No. 2002-239265 filed in Japan on August 20, 2002, the entire contents of which are hereby incorporated by reference.

## BACKGROUND OF THE INVENTIOIN

## 1. Field of the Invention

[0002] The present invention relates to an inflator suitable for an air bag system for an automobile, and an air bag system using the same.

## 2. Description of the Related Art

[0003] In order to optimally protect a passenger in accordance with a position of a seat in a vehicle, such as a driver side, a passenger side and the like, various inflators for an inflating type safety system for an automobile are used. For example, an inflator using a pressurized gas such as argon, helium or the like, as inflating means for an air bag is known. In such an inflator, since an outflow of a pressurized gas is started by rupturing of a rupturable plate and an air bag is inflated and developed thereafter, it is important to improve rupturability of the rupturable plate for improving an operational reliability of the inflator. Further, in order to satisfy a demand for size-reduction and weight-reduction, it is necessary to simplify the structure of the inflator as much as possible and satisfy demands for such as simplification of a manufacturing process and a reliability of an operation over a long period of time.

[0004] An invention relating to an inflator with a stored gas is disclosed in JP-A 2002-172995. In Fig. 2 of this invention, a main chamber and a small chamber are formed, a communication hole and a small hole are formed in a separation wall positioned between these chambers, and a gas ejecting hole and the communication hole formed in the small chamber are respectively mounted with rupturable plates (burst shims). An initiator is disposed in a pressurized atmosphere inside the small chamber, and there is a description that the rupturable plate can be ruptured even by an igniter with a small output. In this inflator, however, there are the following problems.

[0005] In this inflator, in order to maintain a pressurized gas inside the small chamber, it is necessary to seal the initiator securely in order to keep air-tightness, and not to let the gas

- 2 -

inside the small chamber leak from the initiator. However, in view of charging the gas at a high pressure, it is difficult to maintain the air-tightness over a period of 10 years or more which is a life period of a vehicle.

[0006] Further, in paragraph 24 of the specification, there is a description that “P2 is approximately equal to (P1 – Pm) or slightly smaller than the same”. Here, P2 represents a rupturing pressure for the rupturable plate, P1 represents a rupturing pressure for the rupturable plate, and Pm represents a charging pressure of a gas charged in the small chamber and the main chamber. According to the disclosure, the temperature inside the small chamber and the number of moles of the gas rise according to actuation of the initiator. Accordingly, when the pressure in the small chamber becomes higher than that in the main chamber, there are no problems in that two rupturable plates are simultaneously ruptured. However, if the rupturable plate is ruptured first, the pressure inside the small chamber escapes into the main chamber, so that a shock wave generated by the initiator hardly acts on the rupturable plate. As a result, the rupturable plate is not ruptured, and the air bag can not be inflated normally.

[0007] Furthermore, even though the initiator is activated, there is not the rupturable plates in an imaginary extension line of a direction in which the shock wave travels, and accordingly, reliability is poor when it is considered in view of rupture of the rupturable plate.

#### SUMMARY OF THE INVENTION

[0008] The present invention is directed to an inflator which can be activated securely over a long period and in that an assembling work and a mounting work can also be facilitated.

[0009] The present invention provides, as means for solving the above problem, an inflator comprising a cylindrical inflator housing having one end closed and the other end opened, and a diffuser portion connected to the opening portion of the inflator housing and having a gas discharging hole, wherein

a pressurized gas is charged in the inflator housing,

a flat plate-like rupturable plate which closes a gas discharging passage reaching the gas discharging hole and whose portion including the center is ruptured to open the gas discharging passage at the time of activation is provided inside the diffuser portion, and

an igniter for rupturing the rupturable plate is further provided at a position orthogonal to the axial direction of the inflator housing such that an actuating portion of the igniter opposes the center of the rupturable plate inside the diffuser portion.

- 3 -

[0010] Here, the word “orthogonal” means 90°, but it includes a non-orthogonal case, for example, such a case that an igniter is mounted obliquely with an inclination of within  $\pm 10^\circ$  to the axial direction of the inflator housing.

[0011] By setting the arrangements of the igniter and the inflator housing, and the igniter and the rupturable plate in the above manner, the inflator itself can be made compact. Further, rupturability of the rupturable plate can be enhanced, and, by setting a drawing-out direction of a lead wire in the opposite direction to the air bag but in the axial direction of the inflator housing, the lead wire does not interfere with the air bag, and thereby, a mounting work of the inflator can be facilitated.

[0012] In the above-described invention, it is preferable that the rupturable plate and the igniter are arranged such that the central axis of the rupturable plate and the central axis of an operation portion of the igniter are coincident with each other.

[0013] The igniter has an operation portion in which a priming is usually disposed at a distal end portion, and the priming is ignited and burned by a current conduction. As a result, a shock wave, a flame, a gas and the like are generated to rupture the rupturable plate. For this reason, since the shock wave, the flame, and the gas travel in the direction of the central axis of the igniter, rupturability of the rupturable plate can be improved by making the central axes of the rupturable plate and the igniter coincide with each other. Incidentally, as the rupturable plate, a flat plate (for example, a disk) is used. However, the rupturable plate deforms into a bowl-like shape with a pressure caused by the pressurized gas, and therefore, the apex of the bowl-like rupturable plate (the apex of the convex portion, which corresponds the center of the rupturable plate) and the central axis of the operation portion of the igniter are arranged to meet each other.

[0014] It is preferable that the diffuser portion has a gas introducing chamber for introducing the pressurized gas inside the inflator housing, and an igniter accommodating chamber for accommodating the igniter and the gas discharging hole, the respective chambers define the gas discharging passage, and the pressurized gas inside the inflator housing is ejected from the gas discharging hole at the time of activation,

[0015] the gas introducing chamber is a space formed in the axial direction of the inflator housing and has an opening portion which is in communication with the inflator housing, and the igniter accommodating chamber is a space formed in the direction orthogonal to the axial direction of the inflator housing and has an opening portion before mounting the igniter and

- 4 -

[0016] the rupturable plate is inserted from the opening portion of the igniter accommodating chamber and mounted in the igniter accommodating chamber side of the gas discharging passage which communicates the igniter accommodating chamber with the gas introducing chamber.

[0017] In this inflator, the pressurized gas charged into the inflator housing is discharged from the gas discharging hole after passing through the inflator housing, the gas introducing chamber and the igniter accommodating chamber. The inflators described below are the same as the above.

[0018] In this inflator, the igniter accommodating chamber has an opening portion, the rupturable plate is inserted and fixed from the opening portion, and the igniter can further be inserted and fixed, so that an assembling work is facilitated. In order to fix the rupturable plate, such a method can be applied that a step portion is provided in the gas discharging passage connecting the gas introducing chamber and the igniter accommodating chamber and the rupturable plate is welded and fixed at the step portion in the igniter accommodating chamber side. Incidentally, the igniter can be fixed by crimping a peripheral edge of the opening portion after the igniter is inserted from the opening portion of the igniter accommodating chamber.

[0019] Further, by arranging the inflator housing, and the gas introducing chamber, the igniter accommodating chamber and the gas outflow chamber which constituent the diffuser portion, as the above, the central axes of the inflator housing and the diffuser portion do not coincide with each other, but the distance between the two central axes becomes shorter, so that the whole size of the inflator can be made compact.

[0020] It is preferable that the diffuser portion has a gas introducing chamber for introducing the pressurized gas inside the inflator housing, an igniter accommodating chamber for accommodating the igniter and the gas discharging hole, the respective chambers define the gas discharging passage, and the pressurized gas inside the inflator housing is ejected from the gas discharging hole at the time of activation;

the gas introducing chamber is a space formed in the axial direction of the inflator housing and has an opening portion which is in communication with the inflator housing, and the igniter accommodating chamber is a space formed in the direction orthogonal to the axial direction of the inflator housing and has an opening portion before mounting the igniter, and

a cylindrical cup with a bottom is inserted into the gas introducing chamber such that an opening portion thereof is directed to the inflator housing, and a side surface of the cup

- 5 -

forms the rupturable plate which closes the gas discharging passage communicating the igniter accommodating chamber with the gas introducing chamber.

[0021] In this inflator, it is preferable that a shape of the gas introducing chamber and a shape of the cup are in the same shape, and a closed end surface (bottom) of the cup abuts against a closed end surface of the gas introducing chamber.

[0022] In this inflator, since the side surface of the cup forms the rupturable plate, a mounting work of the rupturable plate is made easier than a case of welding and fixing a flat plate. In particular, when the gas introducing chamber and the cup have the same shape, the cup is pressed by the pressurized gas and can hardly move. Further, since part of the integrally formed cup side surface forms the rupturable plate, sealing of the pressurized gas is made more securely as compared with the case of the rupturable plate made of a flat plate (for example, a disk), and a fixing work of the cup is made easy. In order to fix the cup, such a method can be applied that, after the cup is inserted into the gas introducing chamber, a peripheral edge in the opening portion of the cup (preferably, with a flange) is welded and fixed at a step portion of an inlet of the gas introducing chamber.

[0023] Further, by arranging the inflator housing, and the gas introducing chamber and the igniter accommodating chamber which constituent the diffuser portion, as the above, the central axes of the inflator housing and the diffuser portion do not coincide with each other, but the distance between the two central axes becomes shorter, so that the whole size of the inflator can be made compact.

[0024] It is preferable that the diffuser portion has a gas introducing chamber for introducing the pressurized gas inside the inflator housing, an igniter accommodating chamber for accommodating the igniter and the gas discharging hole, the respective chambers define the gas discharging passage, and the pressurized gas inside the inflator housing is ejected from the gas discharging hole at the time of activation,

the gas introducing chamber is a space formed in the a direction orthogonal to the axial direction of the inflator housing and has an opening portion which in communication with the inflator housing, and the igniter accommodating chamber is a space formed in the direction orthogonal to the axial direction of the inflator housing and has an opening portion before mounting the igniter, and

the rupturable plate is inserted from the gas introducing chamber and is mounted in the gas introducing chamber side of the gas discharging passage which communicates the igniter accommodating chamber with the gas introducing chamber.

- 6 -

[0025] In this inflator, since the gas introducing chamber and the igniter accommodating chamber are connected in the same direction, the rupturable plate can be inserted from the opening portion of the gas introducing chamber and fixed, so that an assembling work is facilitated. In order to fix the rupturable plate, such a method can be applied that a step portion is provided in the gas discharging passage connecting the gas introducing chamber and the igniter accommodating chamber and the rupturable plate is welded and fixed at the step portion in the gas introducing chamber side.

[0026] Then, by fixing the rupturable plate from the gas introducing chamber side in this manner, a peripheral edge portion of the welded and fixed rupturable plate resists against the pressure of the pressurized gas, and therefore, the rupturable plate never peels off because of decrease in a fixing strength of the rupturable plate caused by the pressure of the pressurized gas.

[0027] Further, by arranging the inflator housing, and the gas introducing chamber, the igniter accommodating chamber and the gas outflow chamber which constituent the diffuser portion, as the above, the central axes of the inflator housing and the diffuser portion do not coincide with each other, but the distance between the two central axes becomes shorter, so that the whole size of the inflator can be made compact.

[0028] It is preferable that the diffuser portion has a gas introducing chamber for introducing the pressurized gas inside the inflator housing, an igniter accommodating chamber for accommodating the igniter and the gas discharging hole, the respective chambers define the gas discharging passage, and the pressurized gas inside the inflator housing is ejected from the gas discharging hole at the time of activation,

the gas introducing chamber is a space formed in the axial direction of the inflator housing and has an opening portion which in communication with the inflator housing, and the igniter accommodating chamber is a space formed in the direction orthogonal to the axial direction of the inflator housing and has an opening portion before mounting the igniter, and

a substantially cylindrical retainer for holding the igniter is inserted and fixed inside the igniter accommodating chamber, and

the rupturable plate is mounted from the outside of an opening portion in one end of the retainer positioned in the gas discharging passage communicating the igniter accommodating chamber with the gas introducing chamber.

[0029] In this inflator, the rupturable plate is welded and fixed from the outside of the opening portion in one end of the retainer for holding the igniter. Thereby, the rupturable

- 7 -

plate can be welded and fixed in a stage prior to inserting of the retainer into the igniter accommodating chamber, a welding and fixing work is made still easier as compared with the cases of the above respective inflators.

[0030] The retainer fixed with the rupturable plate is inserted into the igniter accommodating chamber such that a portion of the retainer which is attached with the rupturable plate is positioned in the gas introducing chamber side. Then, the peripheral edge portion of the rupturable plate or one end of the retainer which is attached with the rupturable plate is made to contact with the gas discharging passage (preferably, it is made to pressure-contact with the step portion formed on the gas discharging passage), and the contacted portion is resistance-welded, so that an air tightness in the gas introducing chamber can be ensured. an air tightness in the gas introducing chamber can be obtained. In this state, finally, the igniter is fixed by inserting the igniter into the retainer and crimping the peripheral edge in the opening portion of the igniter accommodating chamber.

[0031] Further, by arranging the inflator housing, and the gas introducing chamber and the igniter accommodating chamber which constituent the diffuser portion, as the above, the central axes of the inflator housing and the diffuser portion do not coincide with each other, but the distance between the two central axes becomes shorter, so that the whole size of the inflator can be made compact.

[0032] It is preferable that the diffuser portion has a gas introducing chamber for introducing the pressurized gas inside the inflator housing, an igniter accommodating chamber for accommodating the igniter and the gas discharging hole, the respective chambers define the gas discharging passage, and the pressurized gas inside the inflator housing is ejected from the gas discharging hole at the time of activation,

the gas introducing chamber is a space formed in the axial direction of the inflator housing and has an opening portion which in communication with the inflator housing, and the igniter accommodating chamber is a space formed in the direction orthogonal to the axial direction of the inflator housing and has an opening portion communicating with the outside of the inflator before mounting the igniter, and

the rupturable plate is fixed to one surface of an annular fixture, and the annular fixture is fixed to the gas discharging passage, which communicates the igniter accommodating chamber with the gas introducing chamber, such that the one surface is directed to the gas introducing chamber.

- 8 -

[0033] It is desirable that the annular fixture is provided with an annular projecting portion serving as a welding portion for convenience at the time of being welded and fixed to the gas discharging passage by resistance-welding.

[0034] In this inflator, by using the annular fixture, the annular fixture can be welded and fixed inside the diffuser portion after the annular fixture having the rupturable plate welded and fixed is inserted into the diffuser portion. Therefore, the case of welding and fixing a thicker annular fixture inside the diffuser portion can make a welding work easier as compared with the case of welding and fixing a thin disk-like rupturable plate inside the diffuser portion.

[0035] Further, since the fixture is inserted from the opening portion of the igniter accommodating chamber into the diffuser portion such that a side of the fixture which is mounted with the rupturable plate is directed to the gas introducing chamber, a peripheral edge portion of the welded and fixed rupturable plate resists against the pressure of the pressurized gas, so that the rupturable plate never peels off because of decrease in a fixing strength of the rupturable plate caused by the pressure of the pressurized gas.

[0036] It is preferable that the diffuser portion has a gas introducing chamber for introducing the pressurized gas inside the inflator housing, an igniter accommodating chamber for accommodating the igniter and the gas discharging hole, the respective chambers define the gas discharging passage, and the pressurized gas inside the inflator housing is ejected from the gas discharging hole at the time of activation,

the gas introducing chamber is a space formed in the axial direction of the inflator housing and has an opening portion which in communication with the inflator housing and an opening portion which in communication with the outside of the inflator, before mounting the rupturable plate, and the igniter accommodating chamber is a space formed in the direction orthogonal to the axial direction of the inflator housing and has an opening portion communicating with the outside of the inflator before mounting the igniter, and

the rupturable plate is inserted from the opening portion of the gas introducing chamber which is in communication with the outside of the inflator and is mounted in the gas introducing chamber side of the gas discharging passage which communicates the igniter accommodating chamber with the gas introducing chamber, and the opening portion of the gas introducing chamber which is in communication with the outside of the inflator is closed by a lid portion.



- 9 -

[0037] By providing the communication hole which is in communication with the outside of the inflator in the gas introducing chamber in this manner, it is made easy to insert the rupturable plate from the gas introducing hole to fix the same. Further, by arranging the gas introducing chamber and the igniter accommodating chamber in the above manner, a distance between the central axis of the inflator housing and the central axis of the diffuser portion can be smaller, so that the inflator can be made compact.

[0038] In the respective inventions described above, it is preferable that a lead wire which transmits an actuation signal to the igniter via a connector is connected to the igniter, and a direction in which the lead wire extends is different from the direction of mounting the air bag but it is the axial direction of the inflator housing.

[0039] An inflator comprises a cylindrical housing which has an opening portion at one end and is closed at the other end, provided in the vicinity of the closed surface with a gas outflow chamber having a second gas discharging hole, and the gas outflow chamber is connected to a gas discharging hole at the opening portion of the cylindrical housing and is formed in the axial direction of the inflator housing.

[0040] In this inflator, the pressurized gas charged in the inflator housing is discharged from the second gas discharging hole after passing through the inflator housing, the gas introducing chamber, the igniter accommodating chamber, the gas discharging hole and the gas outflow chamber. By providing such a gas outflow chamber, a mounting work of an air bag to the inflator is facilitated.

[0041] In the above invention, it is preferable that plural second gas discharging hole are formed on a side surface of a gas outflow passage at equal intervals. By forming the gas discharging holes in this manner, even if the pressurized gas is ejected from the gas discharging holes by actuation of the inflator due to a fire or the like during transportation or storage of the inflator, the inflator is prevented from jumping out like a rocket. For example, when there is only a single gas discharging hole, the inflator itself jumps out like a rocket by ejection of the pressurized gas, which is very dangerous.

[0042] As one means for solving the problem, an air bag system comprising actuation signal-outputting means including an impact sensor and a control unit, and a module case accommodating an inflator of the present invention and an air bag.

[0043] According to the inflator of the present invention, an inflator assembling work, an assembling work of an air bag system and a mounting work of the air bag system to a vehicle

- 10 -

are facilitated. Further, an inflator itself can be reduced in size, and rupturability of a rupturable plate can be improved at the time of actuation of the inflator.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0044] Fig 1 is a cross-sectional view of an inflator in an axial direction according to one embodiment of the present invention;

[0045] Fig. 2 is a cross-sectional view of an inflator in an axial direction according to another embodiment of the present invention;

[0046] Fig. 3 is a cross-sectional view of an inflator in an axial direction according to another embodiment of the present invention;

[0047] Fig. 4 is a cross-sectional view of an inflator in an axial direction according to yet another embodiment of the present invention;

[0048] Fig. 5 is a vertical cross-sectional view of a retainer shown in Fig. 4;

[0049] Fig. 6 is a cross-sectional view of an inflator in an axial direction according to yet another embodiment of the present invention;

[0050] Fig. 7 is a cross-sectional view of a rupturable plate mounted to a rupturable plate fixture shown in Fig. 6; and

[0051] Fig. 8 is a cross-sectional view of an inflator in an axial direction according to another embodiment of the present invention.

#### DETAILED DESCRIPTION OF THE PRESENT INVENTION

##### (1) Embodiment 1

[0052] One embodiment of the present invention will be explained with reference to Fig. 1. Fig. 1 is a partial cross-sectional view of an inflator 10 in an axial direction thereof.

[0053] A cylindrical inflator housing 12 has an opening portion at one end and closed at the other end. A pressurized medium comprising an inert gas such as argon or helium, or a nitrogen gas is charged into an inner space 14 at a maximum pressure of about 70,000 kPa.

[0054] The inflator housing 12 can be manufactured by swaging or spinning a pipe, or alternatively, an existent gas tank can be used. In case of swaging or spinning a pipe, the pipe has to be closed to such a state that a small hole, serving as a charging hole for a pressurized medium, is left at the other end of the pipe.

[0055] After the inflator housing 12 is connected to a diffuser portion 20, a pressurized gas is charged through the small hole provided in a periphery wall of the housing 12 or at the

- 11 -

other end of the inflator housing 12, and a sealing pin is inserted therein and welded to the inflator housing 12 to close the housing completely.

[0056] The diffuser portion 20 is connected to an opening portion of the inflator housing 12, and comprises a gas introducing chamber 22, to which the pressurized gas inside the inflator housing 12 is introduced, an igniter accommodating chamber 26 which accommodates an igniter 24, and a gas discharging hole 30.

[0057] In the diffuser portion 20, outer shells defining the gas introducing chamber 22 and the igniter accommodating chamber 26 are formed by a single substantially cylindrical housing (a first housing 51), but the outer shells can be formed by a plurality of housings, each provided for the respective chambers.

[0058] The inflator housing 12 and the diffuser portion 20 are welded and fixed to each other at a peripheral edge portion in the opening portion of the inflator housing 12 and the first housing 51.

[0059] Since the gas introducing chamber 22 is a cylindrical space formed in the same direction as the central axis of the inflator housing 12, and is in communication with the inner space 14 at the opening portion 23, the pressurized gas flows in the gas introducing chamber 22.

[0060] The igniter accommodating chamber 26 is formed in a direction orthogonal to the axial direction of the inflator housing 12, and is provided with the gas discharging hole 30. Further, the igniter accommodating chamber 26 has an opening portion for inserting an igniter 24.

[0061] A step portion 25 having a circular opening portion 27 is provided in a gas discharging passage between the gas introducing chamber 22 and the igniter accommodating chamber 26, and a disk-like rupturable plate 29 is mounted to the step portion 25 in the igniter accommodating chamber 26 side.

[0062] The rupturable plate 29 is inserted through the opening portion of the igniter accommodating chamber 26 and its peripheral edge portion is welded and fixed to the step portion 25. Since the igniter accommodating chamber 26 has the opening portion formed in this manner, the rupturable plate 29 can be inserted and fixed from the opening portion and the igniter 24 can further be inserted and fixed, thereby, facilitating an assembling work.

[0063] Since the circular opening portion 27 is closed by the rupturable plate 29, movement of the pressurized gas from the gas introducing chamber 22 to the igniter accommodating chamber 26 is blocked prior to actuation of the inflator 10.

- 12 -

[0064] The rupturable plate 29 has a disk-like shape before it is mounted, but when it receives a pressure of the pressurized gas after being mounted, and it deforms into a bowl-like shape projecting toward the igniter accommodating chamber 26 as shown in the drawing. An apex of the projecting portion corresponds to the center of the rupturable plate 29 and a portion of the rupturable plate including the center is ruptured to open the closed gas discharging passage.

[0065] The igniter 24 is mounted inside the igniter accommodating chamber 26, and the igniter 24 is inserted from the opening portion, and then, the igniter 24 is fixed by crimping a peripheral edge 32 of the opening portion.

[0066] The igniter 24 is mounted such that it is orthogonal to the axial direction of the inflator housing 12 and a longitudinal central axis of an operation portion in the igniter 24 and the central axis (the axis passing through the projecting apex portion) of the rupturable plate 29 are coincident with each other. Since the operation portion of the igniter 24 and the central portion of the rupturable plate 29 exactly oppose each other, a shock wave, a flame, and a gas concentrate on the central portion of the rupturable plate 29 at the time of actuation of the igniter 24, and thereby, rupturability of the rupturable plate 29 becomes very high.

[0067] A connector 33 is fitted to the igniter 24, and a lead wire 34 for transmitting an actuation signal and a current to the igniter 24 is connected to the connector 33. A direction in which the lead wire 34 extends is different from a mounting direction of the air bag 50, but it is along the axial direction of the inflator housing 12.

[0068] As described in the above, in the inflator 10, the extending direction of the lead wire 34 can be restricted, and therefore, an air bag 50 does not interfere with a wiring work of the lead wire 34 at the time of assembling the air bag system including the inflator 10.

[0069] A gas outflow chamber 28 has an outer shell formed by a cylindrical housing (a second housing) 52, and it is welded and fixed to the first housing 51 of the diffuser portion 20, such that its open end portion covers the gas discharging hole 30. The first housing 51 and the second housing 52 may be formed integrally.

[0070] The gas outflow chamber 28 is formed along the axial direction of the inflator housing 12, and has plural gas discharging holes 36 in a side wall thereof in a distal end portion side. These plural second gas discharging holes 36 are formed in the side wall of the gas outflow chamber 28 at equal intervals. Examples of such a formation are, in the widthwise cross sectional view, four holes at the angles of 90°, six holes at the angles of 60°,

- 13 -

or eight holes at the angles of 45°. An odd number of the holes are also acceptable as long as they are formed at equal intervals.

[0071] By arranging the plural second gas discharging holes 36 at equal intervals in this manner, even when an inflator is accidentally actuated due to a fire or the like during transportation to storage thereof and the pressurized gas is ejected from the second gas discharging holes 36, the inflator is prevented from jumping out like a rocket.

[0072] A screen 35 comprising a wire mesh or the like is arranged inside the gas outflow chamber 28 to cover the second gas discharging holes 36 from the inside. This screen 35 is to prevent broken pieces of the rupturable plate 29 from flowing into the air bag 50.

[0073] In the inflator 10, by arranging the inflator housing 12, and the gas introducing chamber 22, the igniter accommodating chamber 26, and the gas outflow chamber 28 which constitute the diffuser portion 20, as shown in Fig. 1, the central axes of the inflator housing 12 and the diffuser portion 20 (particularly, the gas outflow chamber 28) do not coincide with each other, but the distance between the two central axes can be made shorter, so that the whole size of the inflator 10 can be made compact.

[0074] The gas introducing chamber 22, the igniter accommodating chamber 26, and the gas outflow chamber 28 form a gas discharging passage, and the pressurized gas inside the inflator housing 12 passes through the gas introducing chamber 22 and then through the igniter accommodating chamber to be discharged from the gas discharging hole 30, and it flows into the gas outflow chamber 28. Thereafter, the gas is discharged from the second gas discharging holes 36 through the screen 35 to inflate and develop the air bag 50 mounted to cover the second gas discharging holes 36.

## (2) Embodiment 2

[0075] Another embodiment will be explained with reference to Fig. 2. Fig. 2 is a partial cross-sectional view of an inflator 100 in the axial direction thereof. The inflator 100 shown in Fig. 2 has a structure approximately identical to the inflator 10 shown in Fig. 1, and the same reference numerals as those in Fig. 1 indicate the same members in Fig. 2. The following is a description mainly with respect to a difference in structure from Fig. 1 and a difference in an advantageous effect due to the difference in structure.

[0076] In the gas introducing chamber 22, a cylindrical cup 40 with a bottom having the same outer shape as an inner shape of the gas introducing chamber 22 is inserted to have a closed end surface abutted against a closed end surface of the gas introducing chamber 22, so that an opening portion 41 of the cup is directed towards the inflator housing 12. The cup

- 14 -

40 is welded and fixed to the first housing 51 at a flange 42 provided at a peripheral edge of the opening portion.

[0077] Since the pressurized gas flows inside the cup 40, a portion in the side surface of the cup 40 which opposes a circular opening portion 27 bulges and deforms into a bowl-like shape to form a rupturable plate 29a closing the gas discharging passage (the circular opening portion 27) which communicates the igniter accommodating chamber 26 with the gas introducing chamber 22.

[0078] In the inflator 100, since the side surface of the cup 40 forms the rupturable plate 29a, a mounting work of the rupturable plate is facilitated as compared with a case of welding and fixing a flat plate. In particular, since the inner shape of the gas introducing chamber 22 and the shape of the cup 40 are identical to each other, the cup 40 is pressed by the pressurized gas against the gas introducing chamber 22 and prevented from moving, and further, part of the side surface of the cup 40 forms the integrally formed rupturable plate 29a. Therefore, sealing of the pressurized gas is made more securely as compared with a case of using a flat (for example, a disk) rupturable plate, and a fixing work is made easier.

[0079] In the inflator 100, by arranging the inflator housing 12, and the gas introducing chamber 22, the igniter accommodating chamber 26 and the gas outflow chamber 28 which constitute the diffuser portion 20, as shown in Fig. 2, the central axes of the inflator housing 12 and the diffuser portion 20 (particularly, the gas outflow chamber 28) do not coincide with each other, but the distance between the two central axes can be made shorter, so that the whole size of the inflator 100 can be made compact.

[0080] In the inflator 100, since the operation portion of the igniter 24 and the center (the apex of the projecting portion) of the rupturable plate 29a (the side surface of the cup 40) exactly oppose each other, a shock wave, a flame, and a gas concentrate on the center of the rupturable plate 29a at the time of actuation of the igniter 24, and thereby, rupturability of the rupturable plate 29a becomes very high.

### (3) Embodiment 3

[0081] Another embodiment will be explained with reference to Fig. 3. Fig. 3 is a partial cross-sectional view of an inflator 200 in the axial direction thereof. The inflator 200 shown in Fig. 3 has a structure approximately identical to the inflator 10 shown in Fig. 1, and the same reference numerals as those in Fig. 1 indicate the same members in Fig. 3. The following is a description mainly with respect to a difference in structure from Fig. 1 and a difference in an advantageous effect due to the difference in structure.

- 15 -

[0082] Since a gas introducing chamber 22b is a cylindrical space formed in the direction orthogonal to the central axis of the inflator housing 12 and it is in communication with an inner space 14 at an opening portion 23, a pressurized gas flows into the gas introducing chamber 22b.

[0083] The igniter accommodating chamber 26 is formed in the direction orthogonal to the axial direction of the inflator housing 12, and it has an opening portion for inserting an igniter 24 before mounting of the igniter 24.

[0084] A step portion 25 having a circular opening portion 27 is provided in a gas discharging passage between the gas introducing chamber 22b and the igniter accommodating chamber 26, and a disk-like rupturable plate 29 is welded and fixed to the step portion 25 in the gas introducing chamber 22b side. The rupturable plate 29 has a disk shape before mounting, but it deforms, after mounting, into a bowl-like shape projecting towards the igniter accommodating chamber 26 due to the pressure of the pressurized gas, as shown in the drawing. The apex of the projecting portion is the center of the rupturable plate 29, and a portion of the rupturable portion 29 which includes the center is ruptured at the time of actuation of the inflator 200 to open the closed gas discharging passage.

[0085] The rupturable plate 29 is inserted from the opening portion 23 of the gas introducing chamber 22b and a peripheral edge portion thereof is welded and fixed to the step portion 25. Since the circular opening portion 27 is closed by the rupturable plate 29, the pressurized gas is prevented from moving from the gas introducing chamber 22b to the igniter accommodating chamber 26 before actuation of the inflator 200.

[0086] In the inflator 200, since the gas introducing chamber 22b and the igniter accommodating chamber 26 are connected to each other in the same direction, the rupturable plate 29 can be inserted and fixed from the opening portion 23 of the gas introducing chamber 22b, and thereby, an assembling work is facilitated. Further, by fixing the rupturable plate 29 from the gas introducing chamber 22b side in this manner, an peripheral portion of the welded and fixed rupturable plate 29 resists against the pressure of the pressurized gas, so that the rupturable plate 29 is prevented from peeling off due to decrease in a fixing strength of the rupturable plate 29 caused by the pressure of the pressurized gas.

[0087] In the inflator 200, by arranging the inflator housing 12, and the gas introducing chamber 22b, the igniter accommodating chamber 26 and the gas outflow chamber 28 which constitute the diffuser portion 20, as shown in Fig. 3, the central axes of the inflator housing 12 and the diffuser portion 20 (particularly, the gas outflow chamber 28) do not coincide with

- 16 -

each other, but the distance between the two central axes can be made shorter, so that the whole size of the inflator 200 can be made compact.

[0088] In the inflator 200, since the operation portion of the igniter 24 and the center (the apex of the projecting portion) of the rupturable plate 29 exactly oppose each other, a shock wave, a flame, and a gas concentrate on the center of the rupturable plate 29 at the time of actuation of the igniter 24, and thereby, rupturability of the rupturable plate 29 becomes very high.

#### (4) Embodiment 4

[0089] Another embodiment will be explained with reference to Fig. 4 and Fig. 5. Fig. 4 is a partial cross-sectional view of an inflator 300 in the axial direction thereof, and Fig. 5 is a vertical cross-sectional view of a retainer shown in Fig. 4. An inflator 300 shown in Fig. 4 has a structure approximately identical to the inflator 10 shown in Fig. 1, and the same reference numerals as those in Fig. 1 indicate the same members in Fig. 4. The following is a description mainly with respect to a difference in structure from Fig. 1 and a difference in an advantageous effect due to the difference in structure.

[0090] An approximately cylindrical retainer 60 for holding an igniter 24 is inserted and fixed inside the igniter accommodating chamber 26. The retainer 60 has opening portions 61 and 62 at both ends, and has plural gas passing-through holes 63 serving as gas discharging passages.

[0091] The rupturable plate 29 is welded and fixed to an opening peripheral edge portion 64 of the retainer 60 in the opening portion 62 side from the outside of the retainer in a stage before inserting the retainer 60 in the igniter accommodating chamber 26, and when the retainer 60 is inserted into the igniter accommodating chamber 26, a peripheral edge portion of the rupturable plate 29 is pressed to abut against the step portion 25.

[0092] Since the rupturable plate 29 can be welded and fixed at the stage before inserting the retainer 60 into the igniter accommodating chamber 26 in this manner, a welding and fixing work can be made easier as compared with the respective inflators described above, and an assembling work is also made easier. Further, in addition to the welding and fixing, the peripheral edge portion is welded to the step portion 25 in a state that the peripheral edge portion is interposed between the peripheral edge 64 of the opening portion in the retainer 60 and the step portion 25, so that a resisting force against the pressure of the pressurized gas becomes particularly large, and the rupturable plate 29 is prevented from peeling off due to



- 17 -

decrease in a fixing strength of the rupturable plate 29 caused by the pressure of the pressurized gas.

[0093] The retainer 60 inserted into the igniter accommodating chamber 26 with the rupturable plate 29 fixed, as shown in Fig. 4 is welded and fixed to the step portion 25 and the opening portion peripheral edge 64 (and a peripheral edge portion of the rupturable plate 29) by resistance-welding.

[0094] Since the circular opening portion 27 communicating the gas introducing chamber 22 with the igniter accommodating chamber 26 is closed by the rupturable plate 29, the pressurized gas is prevented from moving from the gas introducing chamber 22 to the igniter accommodating chamber 26 before actuation of the inflator 300. Further, an inner wall surface of the igniter accommodating chamber 26 and the retainer 60 are fixed closely to each other, so that the pressurized gas never leaks from the igniter accommodating chamber 26 to the outside the inflator 300 at the time of actuation.

[0095] In the inflator 300, by arranging the inflator housing 12, and the gas introducing chamber 22, the igniter accommodating chamber 26 and the gas outflow chamber 28 which constitute the diffuser portion 20, as shown in Fig. 4, the central axes of the inflator housing 12 and the diffuser portion 20 (particularly, the gas outflow chamber 28) do not coincide with each other, but the distance between the two central axes can be made shorter, so that the whole size of the inflator 300 can be made compact.

[0096] In the inflator 300, since the operation portion of the igniter 24 and the center (the apex of the projecting portion) of the rupturable plate 29 exactly oppose each other, a shock wave, a flame, and a gas concentrate on the center of the rupturable plate 29 at the time of actuation of the igniter 24, and thereby, rupturability of the rupturable plate 29 becomes very high.

#### (5) Embodiment 5

[0097] Another embodiment will be explained with reference to Fig. 6 and Fig. 7. Fig. 6 is a partial cross-sectional view of an inflator 400 in the axial direction thereof, and Fig. 7 is a cross-sectional view of an annular fixture used in Fig. 6. An inflator 400 shown in Fig. 6 has a structure approximately identical to the inflator 10 shown in Fig. 1, and the same reference numerals as those in Fig. 1 indicate the same members in Fig. 6. The following is a description mainly with respect to a difference in structure from Fig. 1 and a difference in an advantageous effect due to the difference in structure.

- 18 -

[0098] An annular fixture 70 has an annular portion 71 and a central hole 72, and it has, on one surface, an inner annular projecting portion 73 and an outer annular projecting portion 74.

[0099] The rupturable plate 29 is welded and fixed to the inner annular projecting portion 73 from the one surface of the annular fixture 70. The rupturable plate 29 has a disk-like shape before mounting, but after it is mounted to the igniter accommodating chamber 26, the rupturable plate 29 inflates and deforms as shown with a double dotted line due to the pressure of the pressurized gas.

[0100] The annular fixture 70 having the rupturable plate 29 welded and fixed is inserted from an opening portion of the igniter accommodating chamber 26 which is in communication with the outside of the inflator, and it is welded and fixed to the step portion 25 at the outer annular projecting portion 74. At that time, preferably, the annular fixture 70 is mounted to have the side in which the rupturable plate 29 mounted positioned in the gas introducing chamber 22 side, so that the rupturable plate 29 hardly peels off due to the pressure of the pressurized gas.

[0101] By welding the relatively thin rupturable plate 29 to the annular fixture 70 before mounting to the inflator and welding the relatively thick annular fixture 70 after inserting into the diffuser portion in this manner, a welding work is made easier as compared with a case of welding the rupturable plate after inserting into the diffuser portion.

[0102] In the inflator 400, by arranging the inflator housing 12, and the gas introducing chamber 22, the igniter accommodating chamber 26 and the gas outflow chamber 28 which constitute the diffuser portion 20, as shown in Fig. 6, the central axes of the inflator housing 12 and the diffuser portion 20 (particularly, the gas outflow chamber 28) do not coincide with each other, but the distance between the two central axes can be made shorter, so that the whole size of the inflator 400 can be made compact.

[0103] In the inflator 400, since the operation portion of the igniter 24 and the center (the apex of the projecting portion) of the rupturable plate 29 exactly oppose each other, a shock wave, a flame, and a gas concentrate on the center of the rupturable plate 29 at the time of actuation of the igniter 24, and thereby, rupturability of the rupturable plate 29 becomes very high.

#### (6) Embodiment 6

[0104] Another embodiment will be explained with reference to Fig. 8. Fig. 8 is a partial cross-sectional view of an inflator 500 in the axial direction thereof. An inflator 500 shown

- 19 -

in Fig. 8 has a structure approximately identical to the inflator 10 shown in Fig. 1, and the same reference numerals as those in Fig. 1 indicate the same members in Fig. 8. The following is a description mainly with respect to a difference in structure from Fig. 1 and a difference in an advantageous effect due to the difference in structure.

[0105] A mounting state of the rupturable plate 29 in an inflator 500 is similar to that in the inflator 200 shown in Fig. 3, but the inflator 500 is different in mounting procedure from the inflator 200 because of a difference in structure of the gas introducing chamber 22f.

[0106] In Fig. 8, the gas introducing chamber 22f is in communication with only the inner space 14 at the opening portion 23. However, before mounting of the rupturable plate 29, the gas introducing chamber 22f is also in communication with the outside of the inflator until a lid portion 80 is attached to the first opening 51.

[0107] The rupturable plate 29 is inserted from an opening portion of the gas introducing chamber 22f which is in communication with the outside of the inflator and it is welded and fixed at the step portion 25 in the same manner as the inflator 200 shown in Fig. 3. Then, after the opening portion is closed by the lid portion 80, the first housing 51 and the lid portion 80 are welded to each other, and the inside of the gas introducing chamber 22f is kept in an hermetic state.

[0108] With such a structure, the distance between the central axis of the inflator housing 12 and the central axis of the gas outflow chamber can be made shorter as compared with the inflator 200 shown in Fig. 3, so that the whole size of the inflator can be made more compact.

[0109] In the inflator 500, since the operation portion of the igniter 24 and the center (the apex of the projecting portion) of the rupturable plate 29 exactly oppose each other, a shock wave, a flame, and a gas concentrate on the center of the rupturable plate 29 at the time of actuation of the igniter 24, and thereby, rupturability of the rupturable plate 29 becomes very high.

[0110] An air bag system, which incorporates the inflator of the foregoing embodiments shown in Fig. 1 to Fig. 4 may be combined with operation signal-outputting means comprising an impact sensor, a control unit, and a module case in which either of the inflators shown in Fig. 1 to Fig. 4 and an air bag are accommodated.

[0111] The inflator of the present invention can be applied to various inflators such as an air bag inflator for a driver side, an air bag inflator for a passenger side, an air bag inflator for a side collision, an inflator for a curtain air bag, an inflator for a knee-bolster, an inflator for an inflatable seat belt, an inflator for a tubular system and an inflator for a pretensioner.